

Compo Office Direct Indirect

Classic cylindrical design that integrates elegantly into any architecture
 Micro-prismatic diffuser for low-glare UGR<19, purpose-built for office lighting
 Direct only or direct/indirect light distribution, switchable via base button
 Ease of installation with no visible screws
 Interchangeable diffusers for easy maintenance
 Flicker-free built-in driver with Phase dimming or DALI (DT-6)



Product Codes (320mm)	C320-[Colour]2418D-O (Phase Cut) / C320-[Colour]2418D-OD (DALI) — Colour: B/W/G/S
Product Codes (450mm)	C450-[Colour]3022D-O (Phase Cut) / C450-[Colour]3022D-OD (DALI) — Colour: B/W/G/S
Product Codes (600mm)	C600-[Colour]5538D-O (Phase Cut) / C600-[Colour]5538D-OD (DALI) — Colour: B/W/G/S
Product Codes (900mm)	C900-[Colour]907055N-O (Non-dim) / C900-[Colour]907055D-OD (DALI) — Colour: B/W/G/S
Materials	Aluminium, Micro-prismatic diffuser
Finishes	Black / White / Brushed Gold / Brushed Silver
LED Chip	Seoul
Dimensions	Diameter 320/450/600/900mm Height 79mm (all sizes)
Power (320/450/600/900)	24W/18W/10W 30W/22W 55W/38W 90W/70W/55W
Lumen (320/450/600/900)	2400/1800lm 3100/2300lm 5500/4000lm 9000/7000/5500lm
Efficacy	100lm/W
CCT	3000K/4000K Switch as standard, 6500K on request
Dimming	Phase Dimming / DALI (DT-6) (900mm: Non-dim / DALI)
Ratings	IP20 / IK08
Optical	CRI >90 SDCM <3 UGR <19
Beam Angle	90°
Flicker / Stroboscopic	PstLM <0.7 / SVM <0.3
Lifetime	>50,000h L80
Light Distribution	Direct only or Direct/Indirect
Warranty	5 Years

