


CORE XS

The CORE XS simultaneously creates a stylish feature whilst also providing sufficient task lighting. An ideal luminaire for areas with limited ceiling space.

- High CRI – Defining architectural details and finishes.
- Quick connection system – For durability and easy installation.
- Flicker free driver – To prevent eye strain.
- Available in 3 beam angles – For the perfect light application.
- High quality lenses – For superior light emissions.
- Unique finish option – Antique Bronze



DIMENSIONS **W** Ø95mm **H** 105mm

LUMINAIRE OPTIONS

BEAM OPTIONS

60° **STANDARD** 40° 20°

FINISHES

☐ WHITE ☒ BLACK ☐ ANTIQUE BRONZE

BAFFLE FINISHES

☒ BLACK **STANDARD** ☐ WHITE ☐ GOLD

IP OPTIONS

20 **STANDARD** 44

GENERAL SPECIFICATIONS

LED	LUMENS (3000K 4000K)
11W	1200 lm 1300 lm
EFFICACY	Up to 118 Lm/W
COLOUR	3000K, Warm White 4000K, Cool White
MATERIAL	Powder Coated Aluminium
CRI	92+
IP	20
COLOUR DEVIATION	SDCM ≤2
UGR	<18
LIFETIME	> 55,000hrs L90B10
WARRANTY	5 Years

DRIVER SPECIFICATIONS

POWER	300mA 240V Built-In Driver
DIMMING	Phase-Cut / DALI available
POWER FACTOR	> 0.95

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60°	118-CORXS11W603
White, 4000K, 60°	118-CORXS11W604
Black, 3000K, 60°	118-CORXS11B603
Black, 4000K, 60°	118-CORXS11B604
Antique Bronze, 3000K, 60°	118-CORXS11AB603
Antique Bronze, 4000K, 60°	118-CORXS11AB604
White, 3000K, 60°, DALI	118-CORXS11W603D
White, 4000K, 60°, DALI	118-CORXS11W604D
Black, 3000K, 60°, DALI	118-CORXS11B603D
Black, 4000K, 60°, DALI	118-CORXS11B604D
Antique Bronze, 3000K, 60°, DALI	118-CORXS11AB603D
Antique Bronze, 4000K, 60°, DALI	118-CORXS11AB604D

ACCESSORIES

40° Lens	118-LSCX40
20° Lens	118-LSCX20
White Baffle	118-CORXS BW
Gold Baffle	118-CORXS BG
Black Honeycomb Baffle	118-CORXS BHB
White, IP 44 Mounting Plate	118-CORIPKITW
Black, IP 44 Mounting Plate	118-CORIPKITB

