

FUOCO MOVE OUT

355° rotation and 45° tilt for accent or general lighting
 High visual comfort with outstanding colour performance, CRI>97
 Ideal for retail, museums, and presentation lighting



Features and Details

- Minimal design with a thin decorative trim
- 355° rotatable and tiltable into the right direction
- Designed for low glare, high output and long life
- Outstanding colour performance CRI>97, SDCM<3
- Interchangeable reflectors design
- Phase cut dimming, DALI 2 dimming (Flicker Free Driver)
- Suited to residential, retail, hospitality, education or hotel use

Product Code	Fuoco Move Out
Ordering Code Format	FMO-[F]10[A][C]D[-D] (see code key below)
Finish Code (F) / CCT Code (C)	B = Black (RAL 9005), W = White (RAL 9016) / 3 = 3000K, 4 = 4000K
Beam Angle (A) / Dimming Suffix	15° / 24° / 36° / 60° — no suffix = Phase Cut, "-D" = DALI
Example	FMO-B10153D-D = Black, 3000K, 15°, DALI
Material	Aluminium
LED Power / Efficacy	10W / 60lm/W
Lumens	600lm
CRI / SDCM / UGR	>97 / <3 / <19
IP Rating / Insulating Rating	IP20 / IC-4
Lifetime	>50,000h L90
Warranty	5 Years

