## Fuoco Round Surface Adjustable

Product Coded

FRSA - B10315D FRSA - B10324D FRSA - B10336D FRSA - B10360D

#### **DESCRIPTION**

**PURATI** 

IP54 surface mounted adjustable downlight with minimalistic design and versatile application


The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With a minimal design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.



## QUICKINFO

### GENERAL

GENERAL							
Finish Materiall IP							RAL 9010 Aluminiu
Lifespan Warranty		L90/50,000h 5 years					
LED							
Optic Lumen Efficacy CRI CCT SDCM UGR				15°/	24°/3		° Reflecto 915lr to 87lm/\ 3000 >9 < <1
ELECTRICAL Voltago							220-240
Voltage Power							10\
Driver Build-in (Flicker-Free)							Phase cu
ACCESSORIE	S						
Glass diffuser	or ho	neyco	mb lo	uver			
						1	



# Fuoco Round Surface Adjustable

Product Coded

FRSA - W10315D FRSA - W10324D FRSA - W10336D FRSA - W10360D



**PURATI** 

# IP54 surface mounted adjustable downlight with minimalistic design and versatile application


The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With a minimal design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.



## QUICKINFO

#### **GENERAL**

Finish Materiall IP Lifespan Warranty  LED Optic	White (RAL 9016) Die-cast Aluminium 54 L90/50,000h 5 years
Lifespan Warranty  LED Optic	L90/50,000h 5 years
Warranty  LED  Optic	5 years
Optic	15°/24° /36° /60° Reflector
	15°/24° /36° /60° Reflector
	13 / 24 / 30 / 00 TREMEDIO
Lumen	915lm
Efficacy	Up to 87lm/W
CRI	3000K
CCT	>92
SDCM	<3
UGR	<19
ELECTRICAL	
Voltage	220-240V
Power	10W
Driver Build-in	Phase cut
(Flicker-Free)	
4.00F000BIF0	
ACCESSORIES	
Glass diffuser or honeycomb louve	er
BEAM 15°/24°/36°/60°	IK10 IC-4 SARS SARS



PURATI PTY LTD Unit 10, 80 O'Riordan St, Alexandria NSW 2015 Tel: +61 2 8065 8181 sales@purati.com