


# PRO MINI ROUND G3

The Generation 3 FAZE PRO is specifically designed to enhance. Utilising superior LED technology, combined with a high CRI, and a re-engineered heatsink; this series of downlights are guaranteed to bring your spaces to life, in an efficient manner.

- Precision reflector or lens options – for enhanced light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and low glare.
- Generation 3 LED technology.



**DIMENSIONS** **W** Ø84mm **H** 98mm  
**CUT-OUT** **i** Ø76mm

## LUMINAIRE OPTIONS

**LED & LUMENS OPTIONS** (3000K | 4000K)

**10W** 1170lm | 1270lm **8W** 1025lm | 1125lm

**BEAM OPTIONS** (REFLECTOR / LENS)

**60° REFLECTOR** **STANDARD** **60°** **36°** **24°** **15°**

**FINISHES**

**WHITE**  **BLACK**

## GENERAL SPECIFICATIONS

**EFFICACY** Up to 140 Lm/W  
**COLOUR** 3000K, Warm White  
 4000K, Cool White  
**MATERIAL** Powder Coated Material  
**CRI** 92+  
**IP** 44  
**COLOUR DEVIATION** SDCM ≤2  
**UGR** <15  
**LIFETIME** > 55,000hrs L90B10  
**WARRANTY** 7 Years

## DRIVER SPECIFICATIONS

**DIMENSIONS** L 98 x W 38 x H 24  
**POWER** 300mA | 250mA 240V  
 Remote Flicker Free  
 Dimmable Driver  
**DIMMING** Phase Cut Dimming  
**POWER FACTOR** > 0.90

## PROJECT DETAILS

**PROJECT**

**TYPE**

**NOTES**

## PRODUCT CODES

White, 3000K, 60° **118-PR3MR11W603**  
 White, 4000K, 60° **118-PR3MR11W604**  
 Black, 3000K, 60° **118-PR3MR11B603**  
 Black, 4000K, 60° **118-PR3MR11B604**

## ACCESSORIES

36° Reflector **118-RFLP36**  
 24° Reflector **118-RFLP24**  
 15° Reflector **118-RFLP15**  
 60° Lens **118-LSE360**  
 36° Lens **118-LSE336**  
 24° Lens **118-LSE324**  
 15° Lens **118-LSE315**

## DRIVER CODES

**DRIVER SOLD SEPERATELY**

10W **118-300MA**  
 8W **118-250MA**

**DALI DIMMING AVAILABLE UPON REQUEST**

