

SLICE LONG 900 / 1200 / 1500

Minimalist surface-mounted panel light with uniform light distribution

Designed by NPK Design, Netherlands


Push-locking mechanism for easy installation

Can be surface mounted, wall mounted, or suspended

Flicker-free built-in driver

Triac Dimming (1%-100%) / DALI Dimming (DT6)

Ideal for both residential and commercial applications



Product Code — 900mm	SL900-B3224D / SL900-B3224D-D / SL900-W3224D / SL900-W3224D-D / SL900-S3224D / SL900-S3224D-D
Product Code — 1200mm	SL1200-B3829D / SL1200-B3829D-D / SL1200-W3829D / SL1200-W3829D-D / SL1200-S3829D / SL1200-S3829D-D
Product Code — 1500mm	SL1500-B5040D / SL1500-B5040D-D / SL1500-W5040D / SL1500-W5040D-D / SL1500-S5040D / SL1500-S5040D-D
Materials	Polycarbonate
Finishes	Black / White / Silver
Mounting	Surface mounted / Wall mounted / Suspended
Sizes & LED Power	900mm - 32W/24W 1200mm - 38W/29W 1500mm - 50W/40W
Sizes & Lumens	900mm - 3200lm/2400lm 1200mm - 3800lm/2900lm 1500mm - 5000lm/4000lm
Efficacy	100lm/W
CCT	3000K/4000K Switch
Dimming	Triac (1%-100%) / DALI (DT6)
IP Rating	IP54
CRI	>90
SDCM	<3
UGR	<23
Beam Angle	120°
Lifetime	>50,000h L80
Warranty	5 Years

