

# SPLIT

Designed to revolve around any application, the Split ceiling light is minimalist in design and precise in lighting distribution. Highly adaptable, this luminaire is an ideal lighting solution when paired together or used individually, for both residential and commercial applications.

- Innovating rotating lens head.
- High quality aluminium housing.
- Light any surface – Adjustable up to 60°, with 350° rotation.
- Discreet lock-in mount, complimenting its minimalist design.



**DIMENSIONS**      **W** Ø65mm    **H** 200mm

## LUMINAIRE OPTIONS

### BEAM OPTIONS

50° **STANDARD** 36° 25°

### FINISHES

WHITE     BLACK

### BAFFLE FINISHES

WHITE     BLACK     GOLD

### LENS OPTION

CLEAR    **STANDARD**     HONEYCOMB

## GENERAL SPECIFICATIONS

**LED**                      **LUMENS** (3000K | 4000K)

12W                      1085 lm | 1195 lm

**EFFICACY**              Up to 99 Lm/W

**COLOUR**              3000K, Warm White  
4000K, Cool White

**MATERIAL**            Powder Coated Material

**CRI**                      90+

**IP**                        20

**COLOUR DEVIATION**    SDCM ≤3

**UGR**                    <19

**LIFETIME**              > 55,000hrs L80B10

**WARRANTY**            5 Years

## DRIVER SPECIFICATIONS

**POWER**                350mA 240V  
Built-In Driver

**DIMMING**            Phase Cut Dimming

**POWER FACTOR**      > 0.90

**REMOTE DALI DIMMING AVAILABLE UPON REQUEST**

## PROJECT DETAILS

### PROJECT

### TYPE

### NOTES

## PRODUCT CODES

White, 3000K, 50°	<b>83-SP12W503</b>
White, 4000K, 50°	<b>83-SP12W504</b>
Black, 3000K, 50°	<b>83-SP12B503</b>
Black, 4000K, 50°	<b>83-SP12B504</b>

## ACCESSORIES

36° Reflector	<b>83-RFL36</b>
24° Reflector	<b>83-RFL25</b>
Honeycomb Lens	<b>83-AIRH</b>
White Baffle	<b>83-SPLITRW</b>
Black Baffle	<b>83-SPLITRB</b>
Gold Baffle	<b>83-SPLITRG</b>

